

## Lintel Load Tables – Fairfaced Range, suitable for wall thickness of 190mm

The figures in our load tables denote working load and therefore include a safety margin.  
All figures are in kN/m.

Fairfaced Fire Range		Type 19	Type 20	Type 21
Suitable Wall Thickness		190mm	190mm	190mm
Dimensions		190mm x 140mm	190mm x 215mm	190mm x 290mm
Fire Resistance		90mins	90mins	90mins
Suitable for Foundation Use?		Yes	Yes	Yes
Length	Clear Span	kNm	kNm	kNm
900mm	700mm	104.33	128.50	154.40
1100mm	900mm	68.15	103.84	124.74
1200mm	1000mm	56.71	94.72	113.78
1500mm	1200mm	40.97	80.54	96.72
1800mm	1500mm	27.22	59.63	78.90
2100mm	1800mm	18.47	42.42	63.92
2400mm	2100mm	12.19	31.61	47.68
2700mm	2400mm	8.48	24.29	36.83
3000mm	2700mm	6.13	18.75	29.22
3300mm	3000mm	4.57	13.89	23.68
Lintel Weight		63.8kg/m	110.9kg/m	149.6kg/m

King Stone Products Ltd  
Unit 154, Langar Trading Estate  
Harby Road, Langar  
Nottinghamshire  
NG13 9HY

Tel: 01949 831832

Fax: 01949 831841

Email: [enquiries@kingstoneproducts.co.uk](mailto:enquiries@kingstoneproducts.co.uk)

Website: [www.kingstoneproducts.co.uk](http://www.kingstoneproducts.co.uk)

Company Registration Number: 4759305